Title	Maintain aircraft gyroscopic instrument systems		
Level	4	Credits	2

PurposePeople credited with this unit standard are able to: prepare to maintain aircraft gyroscopic instrument systems; locate defect in aircraft gyroscopic instrument systems; restore airworthines of aircraft gyroscopic instrument systems; and complete the maintenance task for aircraft gyroscopic instrument systems.
--

Classification	Aeronautical Engineering > Avionic Maintenance	
Available grade	Achieved	

Guidance Information

- 1 All tasks must be carried out in accordance with enterprise procedures.
- 2 Definition

Enterprise procedures – procedures used by the organisation carrying out the work and applicable to the tasks being carried out. Examples are – standard operating procedures, safety procedures, equipment operating procedures, codes of practice, quality management practices and standards, procedures to comply with legislative and local body requirements.

- 3 Maintenance activities are those usually carried out on an aircraft in a hangar.
- 4 The scope of the system that this standard relates to is described in ATA iSpec 2200, chapter 34.

Outcomes and performance criteria

Outcome 1

Prepare to maintain aircraft gyroscopic instrument systems.

Performance criteria

- 1.1 Task is determined by reviewing maintenance documentation.
- 1.2 Resources are obtained and checked for serviceability or status.

Range may include but is not limited to – publications, tools, equipment, safety equipment, materials.

- 1.3 Aircraft registration and system to be maintained are matched with documentation.
- 1.4 Aircraft and system are prepared for the application of power and for system operation.

Range cockpit controls match component positions, clearances, isolation tags, warning signs.

1.5 Ground and/or support equipment is positioned ready for system operation.

Outcome 2

Locate defects in aircraft gyroscopic instrument systems.

Performance criteria

2.1 Serviceability is determined.

Range inspect, assess, test.

2.2 Defects are reported and documented.

Outcome 3

Restore airworthiness of aircraft gyroscopic instrument systems.

Performance criteria

3.1	Methods of rectifying defects are determined.		
3.2	Replacement parts are procured and verified as authentic and serviceable.		
	Range	identify, inspect.	
3.3	Defects are rectified.		
	Range	may include but is not limited to – repair, replace, modify, adjust, calibrate, lubricate.	
3.4	System is tested to verify serviceability.		
3.5	Inspections are obtained.		
	Range	independent, duplicate, progressive.	

Outcome 4

Complete the maintenance task for aircraft gyroscopic instrument systems.

Performance criteria

- 4.1 Aircraft, system, and work area are left in a state that enables the next task to begin.
- 4.2 Resources are checked for serviceability and returned to service or storage.

Range may include but is not limited to – publications, tools, equipment, safety equipment.

4.3 Leftover parts and materials are disposed of.

Range may include but is not limited to – serviceable, unserviceable, surplus, waste, scrap, hazardous.

4.4 Documentation is completed.

Range may include but is not limited to – labels, work cards, release notes, log books, certification.

Replacement information	This unit standard, unit standard 22529, unit standard 22530, unit standard 22531, unit standard 22532, and unit standard 22534 replaced unit standard 3951.

Planned review date	31 December 2024
---------------------	------------------

Status information and last date for assessment for superseded versions				
Process	Version	Date	Last Date for Assessment	
Registration	1	19 May 2006	31 December 2016	
Review	2	24 October 2014	31 December 2021	
Review	3	26 March 2020	N/A	

Consent and Moderation Requirements (CMR) reference0028This CMR can be accessed at http://www.nzqa.govt.nz/framework/search/index.do.

Comments on this unit standard

Please contact ServiceIQ <u>qualifications@serviceiq.org.nz</u> if you wish to suggest changes to the content of this unit standard.