Title	Maintain aircraft wiring loom and harness assemblies			
Level	4	Credits	25	

Purpose	People credited with this unit standard are able to: prepare to maintain aircraft wiring loom and harness assemblies; locate defects in aircraft wiring loom and harness assemblies; restore airworthiness of aircraft wiring loom and harness assemblies; and complete the maintenance task for aircraft wiring loom and harness assemblies.
---------	--

Classification	Aeronautical Engineering > Avionic Maintenance	
Available grade	Achieved	

Guidance Information

- 1 All tasks must be carried out in accordance with enterprise procedures.
- 2 Definition

Enterprise procedures – procedures used by the organisation carrying out the work and applicable to the tasks being carried out. Examples are – standard operating procedures, safety procedures, equipment operating procedures, codes of practice, quality management practices and standards, procedures to comply with legislative and local body requirements.

- 3 This task is usually carried out on the aircraft.
- 4 This unit standard excludes fibre optic conductors and cabling.
- 5 The scope of the system that this standard relates to is described in the applicable chapters of ATA iSpec 2200.

Outcomes and performance criteria

Outcome 1

Prepare to maintain aircraft wiring loom and harness assemblies.

Performance criteria

1.1 Task is determined by reviewing maintenance documentation.

- 1.2 Resources are obtained and checked for serviceability or status.
 - Range may include but is not limited to publications, tools, equipment, safety equipment, materials.
- 1.3 Aircraft registration and system to be maintained are matched with documentation.
- 1.4 Aircraft and system are prepared for the application of power and for system operation.
 - Range cockpit controls match component positions, clearances, isolation tags, warning signs.
- 1.5 Ground and/or support equipment is positioned ready for system operation.

Outcome 2

Locate defects in aircraft wiring loom and harness assemblies.

Performance criteria

2.1 Serviceability is determined.

Range disassemble, inspect, assess, test.

2.2 Defects are reported and documented.

Outcome 3

Restore airworthiness of aircraft wiring loom and harness assemblies.

Performance criteria

- 3.1 Methods of rectifying defects are determined.
- 3.2 Replacement parts are procured and verified as authentic and serviceable.

Range identify, inspect.

3.3 Defects are rectified.

Range may include but is not limited to – repair, replace, modify, adjust, calibrate.

- 3.4 System is tested to verify serviceability.
- 3.5 Inspections are obtained.

Range independent, duplicate, progressive.

Outcome 4

Complete the maintenance task for aircraft wiring loom and harness assemblies.

Performance criteria

4.1	Aircraft, system, and work area are left in a state that enables the next task to begin.		
4.2	are checked for serviceability and returned to service or storage.		
	Range	may include but is not limited to – publications, tools, equipment, safety equipment.	
4.3 Leftover parts and materials are disposed of.		ts and materials are disposed of.	
	Range	may include but is not limited to – serviceable, unserviceable, surplus, waste, scrap, hazardous.	
4.4	Documentation is completed.		
	Range	may include but is not limited to – labels, work cards, release notes, log books, certification.	

ecember 2024

Status information and last date for assessment for superseded versions

Process	Version	Date	Last Date for Assessment
Registration	1	19 May 2006	31 December 2016
Review	2	24 October 2014	31 December 2021
Review	3	26 March 2020	N/A

Consent and Moderation Requirements (CMR) reference	0028		
This CMR can be accessed at http://www.nzqa.govt.nz/framework/search/index.do.			

Comments on this unit standard

Please contact ServiceIQ <u>qualifications@serviceiq.org.nz</u> if you wish to suggest changes to the content of this unit standard.