

Title	Maintain aircraft liquid oxygen systems		
Level	4	Credits	10

Purpose	People credited with this unit standard are able to: prepare to maintain aircraft liquid oxygen systems; locate defects in aircraft liquid oxygen systems; restore airworthiness of aircraft liquid oxygen systems; and complete the maintenance task for aircraft liquid oxygen systems.
----------------	---

Classification	Aeronautical Engineering > Avionic Maintenance
-----------------------	--

Available grade	Achieved
------------------------	----------

Guidance Information

- 1 All tasks must be carried out in accordance with enterprise procedures.
- 2 Definition
Enterprise procedures – procedures used by the organisation carrying out the work and applicable to the tasks being carried out. Examples are – standard operating procedures, safety procedures, equipment operating procedures, codes of practice, quality management practices and standards, procedures to comply with legislative and local body requirements.
- 3 Maintenance activities are usually carried out on an aircraft in a hangar.
- 4 Systems may include masks and release systems, pressure, demand and flow control converters and regulators, direct and remote reading quantity measuring systems, fixed installation storage, distribution systems.
- 5 The scope of the system that this standard relates to is described in ATA iSpec 2200, chapter 35.

Outcomes and performance criteria

Outcome 1

Prepare to maintain aircraft liquid oxygen systems.

Performance criteria

- 1.1 Task is determined by reviewing maintenance documentation.

- 1.2 Resources are obtained and checked for serviceability or status.
- Range may include but is not limited to – publications, tools, equipment, safety equipment.
- 1.3 Aircraft registration and system to be maintained are matched with documentation.
- 1.4 Aircraft and system are prepared for the application of power and for system operation.
- Range cockpit controls match component positions, clearances, isolation tags, warning signs.
- 1.5 Ground and/or support equipment is positioned ready for system operation.

Outcome 2

Locate defects in aircraft liquid oxygen systems.

Performance criteria

- 2.1 Serviceability is determined.
- Range inspect, assess, test.
- 2.2 Defects are reported and documented.

Outcome 3

Restore airworthiness of aircraft liquid oxygen systems.

Performance criteria

- 3.1 Methods of rectifying defects are determined.
- 3.2 Replacement parts are procured and verified as authentic and serviceable.
- Range identify, inspect.
- 3.3 Defects are rectified.
- Range may include but is not limited to – repair, replace, modify, adjust, calibrate, lubricate.
- 3.4 System is tested to verify serviceability.
- 3.5 Inspections are obtained.
- Range independent, duplicate, progressive.

Outcome 4

Complete the maintenance task for aircraft liquid oxygen systems.

Performance criteria

4.1 Aircraft, system, and work area are left in a state that enables the next task to begin.

4.2 Resources are checked for serviceability and returned to service or storage.

Range may include but is not limited to – publications, tools, equipment, safety equipment.

4.3 Leftover parts and materials are disposed of.

Range serviceable, unserviceable, surplus, waste, scrap, hazardous.

4.4 Documentation is completed.

Range labels, work cards, release notes, log books, certification.

Planned review date	31 December 2024
----------------------------	------------------

Status information and last date for assessment for superseded versions

Process	Version	Date	Last Date for Assessment
Registration	1	19 May 2006	31 December 2016
Review	2	24 October 2014	31 December 2021
Review	3	26 March 2020	N/A

Consent and Moderation Requirements (CMR) reference	0028
--	------

This CMR can be accessed at <http://www.nzqa.govt.nz/framework/search/index.do>.

Comments on this unit standard

Please contact ServicelQ qualifications@serviceiq.org.nz if you wish to suggest changes to the content of this unit standard.