

Title	Demonstrate knowledge of resilient flooring products		
Level	3	Credits	8

Purpose	People credited with this standard are able to describe: the composition and purpose of resilient flooring products; the manufacturing process of resilient flooring products; and the installation and performance of resilient flooring products.
----------------	---

Classification	Construction Trades > Flooring
-----------------------	--------------------------------

Available grade	Achieved
------------------------	----------

Guidance Information

- 1 Performance of the outcomes of this unit standard must comply with the following legislation and guides: the Building Act 2004; Health and Safety in Employment Act 1992; *A Guide to the Health and Safety in Employment Act 1992 (2003 – 2nd edition)*, published by the Department of Labour and available at <http://www.osh.dol.govt.nz>; and their subsequent amendments.
- 2 *Workplace procedures* are all authorised instructions, processes and work practices carried out in the workshop, factory, shop and worksite.

Outcomes and performance criteria

Outcome 1

Describe the composition and purpose of resilient flooring products.

Performance criteria

- 1.1 The description identifies resilient flooring products' components in accordance with manufacturers' specifications.

Range includes but is not limited to – tiles, sheet.
- 1.2 The description explains the benefits and drawbacks of using resilient flooring products in accordance with manufacturers' specifications and workplace procedures.

Range may include but is not limited to – aesthetic appeal, longevity, space and traffic considerations.

Outcome 2

Describe the manufacturing process of resilient flooring products.

Performance criteria

- 2.1 The description outlines two different manufacturing processes in accordance with manufacturers' specifications and workplace procedures.
- 2.2 The description outlines two different types of finishing processes in accordance with manufacturers' specifications.

Outcome 3

Describe the installation and performance of resilient flooring products.

Range resilient flooring products include but are not limited to – heterogeneous PVC, homogeneous PVC, linoleum, rubber, thermoplastic tiles.

Performance criteria

- 3.1 The description includes an outline of installation in accordance with manufacturers' specifications.
- Range may include but is not limited to – installation time, method(s), surface preparation; one installation method is required.
- 3.2 The explanation includes an outline of performance characteristics in accordance with manufacturers' specifications.
- Range may include but is not limited to – hardness, stability, appearance, wear time.

Replacement information

This unit standard was replaced by unit standard 32529.

This unit standard is expiring. Assessment against the standard must take place by the last date for assessment set out below.

Status information and last date for assessment for superseded versions

Process	Version	Date	Last Date for Assessment
Registration	1	29 May 2000	31 December 2023
Revision	2	18 February 2004	31 December 2023
Review	3	26 March 2007	31 December 2024
Review	4	25 November 2021	31 December 2024
Rollover	5	30 November 2023	31 December 2024

Consent and Moderation Requirements (CMR) reference

0175

This CMR can be accessed at <http://www.nzqa.govt.nz/framework/search/index.do>.