

<b>Title</b>	<b>Demonstrate knowledge of resilient flooring products</b>		
<b>Level</b>	<b>3</b>	<b>Credits</b>	<b>8</b>

<b>Purpose</b>	People credited with this standard are able to describe: the composition and purpose of resilient flooring products; the manufacturing process of resilient flooring products; and the installation and performance of resilient flooring products.
----------------	---

<b>Classification</b>	Construction Trades > Flooring
-----------------------	--------------------------------

<b>Available grade</b>	Achieved
------------------------	----------

### Guidance Information

- Performance of the outcomes of this unit standard must comply with the following legislation and guides: the Building Act 2004; Health and Safety in Employment Act 1992; *A Guide to the Health and Safety in Employment Act 1992 (2003 – 2<sup>nd</sup> edition)*, published by the Department of Labour and available at <http://www.osh.dol.govt.nz>; and their subsequent amendments.
- Workplace procedures* are all authorised instructions, processes and work practices carried out in the workshop, factory, shop and worksite.

### Outcomes and performance criteria

#### Outcome 1

Describe the composition and purpose of resilient flooring products.

#### Performance criteria

- The description identifies resilient flooring products' components in accordance with manufacturers' specifications.
 

Range includes but is not limited to – tiles, sheet.
- The description explains the benefits and drawbacks of using resilient flooring products in accordance with manufacturers' specifications and workplace procedures.
 

Range may include but is not limited to – aesthetic appeal, longevity, space and traffic considerations.

## Outcome 2

Describe the manufacturing process of resilient flooring products.

### Performance criteria

- 2.1 The description outlines two different manufacturing processes in accordance with manufacturers' specifications and workplace procedures.
- 2.2 The description outlines two different types of finishing processes in accordance with manufacturers' specifications.

## Outcome 3

Describe the installation and performance of resilient flooring products.

Range resilient flooring products include but are not limited to – heterogeneous PVC, homogeneous PVC, linoleum, rubber, thermoplastic tiles.

### Performance criteria

- 3.1 The description includes an outline of installation in accordance with manufacturers' specifications.

Range may include but is not limited to – installation time, method(s), surface preparation; one installation method is required.

- 3.2 The explanation includes an outline of performance characteristics in accordance with manufacturers' specifications.

Range may include but is not limited to – hardness, stability, appearance, wear time.

<b>Replacement information</b>	This unit standard was replaced by unit standard 32529.
--------------------------------	---

**This unit standard is expiring. Assessment against the standard must take place by the last date for assessment set out below.**

### Status information and last date for assessment for superseded versions

Process	Version	Date	Last Date for Assessment
Registration	1	29 May 2000	31 December 2023
Revision	2	18 February 2004	31 December 2023
Review	3	26 March 2007	31 December 2023
Review	4	25 November 2021	31 December 2023

<b>Consent and Moderation Requirements (CMR) reference</b>	0175
--	------

This CMR can be accessed at <http://www.nzqa.govt.nz/framework/search/index.do>.

This unit standard is expiring