

Fix flat fibrous plaster sheets to surfaces

Level 2

Credits 8

Purpose People credited with this unit standard are able to fix flat fibrous plaster sheets to surface areas, and clean up after work is completed.

Subfield Construction Trades

Domain Fibrous Plaster

Status Registered

Status date 20 April 2006

Date version published 25 January 2008

Planned review date 31 December 2011

Entry information Open.

Replacement information This unit standard replaced unit standard 4320 and unit standard 4321.

Accreditation Evaluation of documentation and visit by NZQA and industry.

Standard setting body (SSB) Building and Construction Industry Training Organisation

Accreditation and Moderation Action Plan (AMAP) reference 0048

This AMAP can be accessed at <http://www.nzqa.govt.nz/framework/search/index.do>.

Special notes

- 1 Credit for this unit standard can be achieved on site through a registered assessor, or off site with an accredited training provider.

- 2 All work practices must comply with the following:
Health and Safety in Employment Act 1992;
Health and Safety in Employment Regulations 1995;
Resource Management Act 1991;
Building Act 2004;
AS/NZS 2589:2007 *Gypsum linings – Application and finishing*, available from Standards NZ (<http://www.standards.co.nz>);
Approved Code of Practice for the Safe Erection and Use of Scaffolding (Wellington: Occupational Safety and Health Service, Department of Labour, 1995) available at <http://www.osh.govt.nz>;
New Zealand Building Code.

Elements and performance criteria

Element 1

Fix flat fibrous plaster sheets to surface areas.

Performance criteria

- 1.1 Access is arranged and complies with the Health and Safety in Employment Regulations 1995.
- 1.2 Sheet sizes are determined from work measure and order list.
- 1.3 Sheets are trimmed for jointing methods specified, projections and recesses.
- 1.4 Temporary support systems are selected and used as required by the site conditions.
- 1.5 Sheets are fixed to framing or backing as specified by manufacturer.
Range nails, screws, adhesives, wadding; combination.
- 1.6 All operations are completed without damage to the workplace, tools or plant.

Element 2

Clean up after work is completed.

Performance criteria

- 2.1 Tools and plant are maintained, cleaned and stored in accordance with site practice.
- 2.2 Waste material is disposed of and workplace is cleaned in accordance with site practice.

Please note

Providers must be accredited by NZQA, or an inter-institutional body with delegated authority for quality assurance, before they can report credits from assessment against unit standards or deliver courses of study leading to that assessment.

Industry Training Organisations must be accredited by NZQA before they can register credits from assessment against unit standards.

Accredited providers and Industry Training Organisations assessing against unit standards must engage with the moderation system that applies to those standards.

Accreditation requirements and an outline of the moderation system that applies to this standard are outlined in the Accreditation and Moderation Action Plan (AMAP). The AMAP also includes useful information about special requirements for organisations wishing to develop education and training programmes, such as minimum qualifications for tutors and assessors, and special resource requirements.

Comments on this unit standard

Please contact the Building and Construction Industry Training Organisation national.office@bcito.org.nz if you wish to suggest changes to the content of this unit standard.