

Title	Select materials, and install angle posts		
Level	4	Credits	6

Purpose	People credited with this unit standard are able to: select angle post, block, stay, foots, and footing wire; and install angle posts.
----------------	--

Classification	Agriculture > Fencing
-----------------------	-----------------------

Available grade	Achieved
------------------------	----------

Guidance Information

- 1 Manuals relating to the safe use of equipment are available from manufacturers and should be consulted in all teaching and training situations.
- 2 Legislation relevant to this unit standard includes but is not limited to the Health and Safety at Work Act 2015, and its subsequent amendments.

Outcomes and performance criteria

Outcome 1

Select angle post, block, stay, foots, and footing wire.

Performance criteria

- 1.1 Weak and damaged materials are identified, and selected materials are rot resistant.
- 1.2 Selection of angle post, block, stay, foots, and footing wire are consistent with fence design and use.

Outcome 2

Install angle posts.

Performance criteria

- 2.1 Personal protection equipment appropriate to the task is selected and used according to manufacturer's specifications and Health and Safety in Employment Act requirements.
- 2.2 The angle post is true to given height + or – 10mm, plumb to 20mm maximum lay back at final loading.

- 2.3 The foot is installed in accordance with ground conditions to meet final fence loading, and angle post is firmly rammed.
- 2.4 Angle end of stay is positioned centre of angle post width, in accordance with contour.
- 2.5 Angle head trimmed in proportion with angle diameter and maximising bearing surface, trim cuts of equal length, and all chainsaw marks removed.
- 2.6 The stay angle bisects the angle of the fenceline.
- 2.7 The mortice depth is at 15mm, and size matches stay end.
- 2.8 Block end of stay is positioned in centre of block's length and width, and the stay end face and block face fit square to each other, with block positioned square to stay and horizontally positioned to ensure solid bearing surface.

Replacement information	This unit standard, unit standard 24838, and unit standard 24839 replaced unit standard 19130.
--------------------------------	--

This unit standard is expiring. Assessment against the standard must take place by the last date for assessment set out below.

Status information and last date for assessment for superseded versions

Process	Version	Date	Last Date for Assessment
Registration	1	22 August 2008	31 December 2022
Review	2	29 April 2021	31 December 2022

Consent and Moderation Requirements (CMR) reference	0052
--	------

This CMR can be accessed at <http://www.nzqa.govt.nz/framework/search/index.do>.