

## Fit trim to upholstery

**Level** 3

**Credits** 4

**Purpose** People credited with this unit standard are able to prepare to fit, and fit, trim to upholstery.

**Subfield** Furniture

**Domain** Upholstery

**Status** Registered

**Status date** 19 June 2009

**Date version published** 19 June 2009

**Planned review date** 31 December 2014

**Entry information** Open.

**Replacement information** This unit standard and unit standard 25576 replaced unit standard 2190.

**Accreditation** Evaluation of documentation and visit by NZQA and industry.

**Standard setting body (SSB)** Competenz

**Accreditation and Moderation Action Plan (AMAP) reference** 0173

This AMAP can be accessed at <http://www.nzqa.govt.nz/framework/search/index.do>.

---

### Special notes

- 1 This unit standard must be assessed against on-job.
- 2 Definition  
*Worksite policies and procedures* refer to documented policies and to documented or other directions provided to staff. These may include, but are not limited to, ways of managing health and safety, environmental considerations, quality, and production, and must conform to legislation. Examples include standard operating procedures, company health and safety plans, on-site briefings, and supervisor's instructions.

---

### Elements and performance criteria

#### Element 1

Prepare to fit trim to upholstery.

**Performance criteria**

- 1.1 Job specifications are obtained and explained in accordance with worksite policies and procedures.  
  
Range type of trim, method of attachment, number of items.
- 1.2 A method of fitting types of trim is explained in accordance with worksite policies and procedures.  
  
Range one of – gimp, decorative nails, double piping, banding.
- 1.3 Trim and fitting materials are selected in accordance with job specifications and worksite policies and procedures.

**Element 2**

Fit trim to upholstery.

**Performance criteria**

- 2.1 Trim is measured and cut to avoid waste in accordance with job specifications.
- 2.2 Trim is positioned and securely fixed to upholstery in accordance with job specifications.  
  
Range no visible attachments, in line with frame or markings, ends finished to prevent fraying, ends finished so joins are not noticeable.
- 2.3 Work area is left clean, clear, and safe in accordance with worksite policies and procedures.

---

**Please note**

Providers must be accredited by NZQA, or an inter-institutional body with delegated authority for quality assurance, before they can report credits from assessment against unit standards or deliver courses of study leading to that assessment.

Industry Training Organisations must be accredited by NZQA before they can register credits from assessment against unit standards.

Accredited providers and Industry Training Organisations assessing against unit standards must engage with the moderation system that applies to those standards.

Accreditation requirements and an outline of the moderation system that applies to this standard are outlined in the Accreditation and Moderation Action Plan (AMAP). The AMAP also includes useful information about special requirements for organisations wishing to develop education and training programmes, such as minimum qualifications for tutors and assessors, and special resource requirements.

---

**Comments on this unit standard**

Please contact the Competenz [info@competenz.org.nz](mailto:info@competenz.org.nz) if you wish to suggest changes to the content of this unit standard.