

Title	Apply special effects to signs using airbrush		
Level	4	Credits	20

Purpose	<p>This unit standard is for experienced people working in the signmaking industry.</p> <p>People credited with this unit standard are able to apply special effects to signs using airbrush.</p>
----------------	---

Classification	Printing > Signmaking
-----------------------	-----------------------

Available grade	Achieved
------------------------	----------

Guidance Information

1 Definitions

Company procedures refer to the documented procedures used by the organisation carrying out the work and applicable to the tasks being carried out. They may include but are not limited to – standard operating procedures, site safety procedures, equipment operating procedures, codes of practice, quality assurance procedures, housekeeping standards, charging of time and materials, management of drawings and documentation, procedures to comply with legislative and local body requirements.

Accepted industry practice refers to codes of practice and standardised procedures accepted by the wider signmaking industry as examples of best practice.

Job requirements refer to the information provided about the agreed work to be completed.

2 Range

Evidence is required of a minimum of two different signs.

Outcomes and performance criteria

Outcome 1

Apply special effects to signs using airbrush.

Performance criteria

- 1.1 Area to be painted is identified and masked on the surface in accordance with job requirements.

- 1.2 Area to be left unpainted is masked with a masking material suitable for the task in accordance with job requirements.
- Range masking material may include but is not limited to – tape and paper, vinyl, masking film.
- 1.3 Surface condition is clean, dry, dust and grease free, and masking edges are firm in accordance with job requirements.
- 1.4 Coating system selected is compatible with the surface material and complies with the job specifications in accordance with company procedures and accepted industry practice.
- Range coating system may include but is not limited to – water-based acrylic, enamel, lacquer, base coat, clear coat.
- 1.5 Primer is applied to provide key and opacity in accordance with job specifications, company procedures, and accepted industry practice.
- 1.6 Surface is prepared and finish coats applied in accordance with manufacturer requirements, job specifications, company procedures, and industry practice.
- 1.7 Stencils are selected and cut in accordance with job specifications, company procedures, and accepted industry practice.
- 1.8 Final colours and detailing are applied in accordance with job specifications, company procedures and accepted industry practice.
- 1.9 Protective coating is applied without damage to completed artwork in accordance with job specifications, company procedures, and accepted industry practice.

This unit standard is

Replacement information	This unit standard replaced unit standard 1061 and unit standard 20192.
--------------------------------	---

This unit standard is expiring. Assessment against the standard must take place by the last date for assessment set out below.

Status information and last date for assessment for superseded versions

Process	Version	Date	Last Date for Assessment
Registration	1	19 January 2012	31 December 2016
Revision	2	16 April 2015	31 December 2022
Review	3	20 April 2017	31 December 2022
Rollover	4	17 August 2017	31 December 2022

Consent and Moderation Requirements (CMR) reference	0005
--	------

This CMR can be accessed at <http://www.nzqa.govt.nz/framework/search/index.do>.

**This unit standard is
expiring**