Title	Diagnose and repair traction motor system faults in electric vehicles				
Level	5		Credits	10	
Purpose		People credited with this unit standard are able to diagnose and repair faults in traction motor systems in electric vehicles.			
Classification		Motor Industry > Automotive Electrical and Electronics			
Available grade		Achieved			
Prerequisites		Unit 31416, <i>Dep</i> demonstrate equ		<i>alise electric vehicles,</i> or knowledge.	

Guidance Information

- Evidence presented for assessment against this unit standard must be consistent with safe working practices and be in accordance with applicable service information, company requirements and legislative requirements. This includes the knowledge and use of suitable tools and equipment.
- 2 Legislation, regulations and/or industry standards relevant to this unit standard include but are not limited to the Health and Safety at Work Act 2015; and any subsequent amendments and replacements.
- Competency under this unit standard does not entitle the learner to legally perform prescribed electrical work. Any prescribed electrical work must be undertaken by a person who has been registered and licensed under the Electricity Act 1992. Prescribed electrical work is defined in Schedule 1 of the Electricity (Safety) Regulations 2010.
- 4 Electric vehicles may be hybrid or battery electric. Hybrid electric vehicles may include – plug in hybrid electric vehicles (PHEV), fuel cell electric vehicles (FCEV), additional new hybrid technology. Battery electric vehicles may include – range extended electric vehicles (REEV), additional new electric vehicle technology.
- 5 Definitions

Company requirements refer to instructions to staff on policy and procedures that are available in the workplace. These requirements may include – company policies and procedures, work instructions, product quality specifications and legislative requirements.

Repair refers to replacement, adjustment or repairs as required.

Service information may include – technical information for a vehicle, machine, or product detailing operation; installation and servicing procedures; manufacturer instructions; technical terms and descriptions; and detailed illustrations. High Voltage (HV) refers to voltages above 60 V. Low Voltage (LV) refers to voltages below 60 V.

Outcomes and performance criteria

Outcome 1

Diagnose traction motor system faults.

Range may include speed control, motor, circuit.

Performance criteria

1.1 Traction motor system faults are diagnosed.

Range may include – HV system powered up, HV system powered down.

Outcome 2

Repair traction motor system faults.

Range may include – speed control, motor, circuit.

Performance criteria

- 2.1 LV supply is disconnected and the proximity key is removed and secured.
- 2.2 HV service plug or manual service disconnect is removed and secured to depower the HV system.
- 2.3 HV system is measured for zero residual AC and DC voltage.
- 2.4 Traction motor system faults are repaired.
- 2.5 HV service plug or manual service disconnect is reconnected.
- 2.6 LV supply is reconnected and the system is powered up.

Planned review date	31 December 2023
---------------------	------------------

Status information and last date for assessment for superseded versions

Process	Version	Date	Last Date for Assessment
Registration	1	27 September 2018	N/A

Consent and Moderation Requirements (CMR) reference	0014
Consent and Moderation Neganiemes (CMIN) reference	00 1 4

This CMR can be accessed at http://www.nzga.govt.nz/framework/search/index.do.

Comments on this unit standard

Please contact MITO New Zealand Incorporated info@mito.org.nz if you wish to suggest changes to the content of this unit standard.