

<b>Title</b>	<b>Install a splashback and mirror glazing application</b>		
<b>Level</b>	<b>4</b>	<b>Credits</b>	<b>3</b>

<b>Purpose</b>	<p>A person credited with this standard can:</p> <ul style="list-style-type: none"> <li>• complete a site measure and plan for installation of splashback and mirror glazing;</li> <li>• install a splashback and mirror glazing application; and</li> <li>• complete cleaning and storage requirements.</li> </ul>
----------------	---

<b>Classification</b>	Construction Trades > Glazing
-----------------------	-------------------------------

<b>Available grade</b>	Achieved
------------------------	----------

---

## Guidance Information

### 1 Assessment

This unit standard must be assessed under the supervision of a commercially competent glazing practitioner in workplace conditions that reflect:

- current health, safety, industry, and workplace requirements; and
- industry requirements for commercially acceptable timeframes.

Evidence generated for assessment against this standard must be verified by a person who has current expertise in the glazing trades and has had the opportunity to regularly observe the candidate in the workplace.

### 2 Definitions

*Personal protective equipment* refers to anything used or worn by a person (including clothing) to minimise risks to the person's health and safety.

*Splashback* is a glass cladding mounted on a wall to provide an aesthetic element to a structure and to protect the wall.

*Worksite requirements* refer to instructions to staff on policy and procedures which are documented in manual format and are available in the workplace. These requirements include – company specifications and procedures, work instructions, manufacturer's specifications, product quality specifications, legislative requirements.

### 3 Installations must be completed without injury to personnel or damage to products and equipment. Personal protective equipment must be used to meet regulatory and worksite requirements.

- 4 Evidence generated for assessment against this standard must reflect the best practice guidelines and principles specified in:
- NZS 4223.1:2008. *Glazing in buildings – Part 1: Code of practice for glazing in buildings - Glass selection and glazing*;
  - NZS 4223.3:2016. *Glazing in buildings – Part 3: Human impact safety requirements*;
  - AS/NZS 4668:2000. *Glossary of terms used in the glass and glazing industry*.
- AS/NZS and NZS standards are available at <http://www.standards.govt.nz>.

---

## Outcomes and performance criteria

### Outcome 1

Complete a site measure and plan for installation of splashback and mirror glazing.

#### Performance criteria

- 1.1 Confirm customer requirements and job specifications before beginning work.
- Range scope of work, location of job, location of services, site access, fixing method, materials and quantities.
- 1.2 Locate electrical and plumbing services before installation.
- 1.3 Prepare an installation plan using information about customer requirements, job specifications, and location of hidden services.
- 1.4 Prepare drawings and or templates suitable for glass ordering according to aesthetic considerations.

### Outcome 2

Install a splashback and mirror glazing application.

Range multiple glass panels on adjacent walls, cut-outs, corner and centre notches, printed splashbacks over multiple panels.

#### Performance criteria

- 2.1 Check and gather equipment, tools, and installation materials before work begins.
- 2.2 Check splashbacks and mirrors for faults before installation.
- Range scratches, silver faults, edge damage, glass faults, edge seal damage.
- 2.3 Resolve any faults.
- 2.4 Confirm that the wall is flat and square and address any inconsistencies.

2.5 Select and apply adhesives compatible with mounting surface and splashback or mirror backing.

2.6 Fix splashbacks and mirrors according to the installation plan.

Range fixing methods include – adhesive and tape, screws, metal channelling, mirror pads.

2.7 Complete installation quality checks.

Range checks include – panels are square, plumb, and secure; drainage and/or freely ventilated airspace between the splashback or mirror and wall meets the job specifications and worksite requirements, silicone joints adherence and free of airgaps, aesthetic elements printed panels meet specifications.

2.8 Provide information to the client about maintenance requirements.

### Outcome 3

Complete cleaning and storage requirements.

### Performance criteria

3.1 Clean and store tools and plant used to install splashbacks and mirrors.

Range plant may include – any machinery, vehicle, equipment (including personal protective equipment) used in a glazing operation.

3.2 Clean the installation and clear and clean the work area.

<b>Planned review date</b>	31 December 2027
----------------------------	------------------

### Status information and last date for assessment for superseded versions

Process	Version	Date	Last Date for Assessment
Registration	1	24 November 2022	N/A

<b>Consent and Moderation Requirements (CMR) reference</b>	0048
--	------

This CMR can be accessed at <http://www.nzqa.govt.nz/framework/search/index.do>.

### Comments on this unit standard

Please contact Waihangara Ara Rau Construction and Infrastructure Workforce Development Council at [qualifications@waihangaraarau.nz](mailto:qualifications@waihangaraarau.nz) if you wish to suggest changes to the content of this unit standard.