

<b>Title</b>	<b>Apply trim to aircraft interior panels</b>		
<b>Level</b>	<b>4</b>	<b>Credits</b>	<b>4</b>

<b>Purpose</b>	People credited with this unit standard are able to: prepare to apply trim to aircraft interior panels; apply trim to interior panel surface; and complete finishing activities related to the application of trim to interior panels.
----------------	--

<b>Classification</b>	Aeronautical Engineering > Aircraft Furnishings and Equipment
-----------------------	---

<b>Available grade</b>	Achieved
------------------------	----------

---

### Guidance Information

- 1 All tasks must be carried out in accordance with enterprise procedures.
- 2 Definition  
*Enterprise procedures* – procedures used by the organisation carrying out the work and applicable to the tasks being carried out. Examples are – standard operating procedures, safety procedures, equipment operating procedures, codes of practice, quality management practices and standards, procedures to comply with legislative and local body requirements.
- 3 The scope of the system that this standard relates to is described in ATA iSpec 2200, chapter 25.
- 4 Aircraft interior panels may include partitions, window surrounds, ceiling panels, storage bins.

---

### Outcomes and performance criteria

#### Outcome 1

Prepare to apply trim to aircraft interior panels.

#### Performance criteria

- 1.1 Task is determined by reviewing maintenance documentation and enterprise procedures.
- 1.2 Work area is prepared, and resources are obtained and checked for serviceability or status.

Range may include but is not limited to – publications, tools, materials, equipment, safety equipment.

1.3 Pattern is fabricated to meet task requirements.

1.4 Trim is cut to meet task requirements.

## **Outcome 2**

Apply trim to interior panel surface.

### **Performance criteria**

2.1 Interior panel surfaces are prepared.

Range may include but is not limited to – clean, apply adhesive.

2.2 Trim is applied to meet specifications.

Range may include but is not limited to – adhesive cured, pressure applied, temperature controlled, excess trim removed.

2.3 Any defects are rectified.

2.4 Inspections are obtained.

Range independent, duplicate, progressive.

## **Outcome 3**

Complete finishing activities related to the application of trim to interior panels.

### **Performance criteria**

3.1 Interior panel is prepared for storage, transit, or use.

3.2 Completion activities specific to the task and work area are carried out.

Range may include but is not limited to – tool control, cleanliness, tidiness, return of publications, preparation for next activity.

3.3 Resources are checked for serviceability and returned to service or storage.

Range may include but is not limited to – tools, equipment, safety equipment, specifications, drawings.

3.4 Leftover items, parts, and materials are disposed of.

Range may include but is not limited to – serviceable, unserviceable, surplus, waste, scrap, hazardous.

3.5 Documentation is completed.

<b>Planned review date</b>	31 December 2027
----------------------------	------------------

#### Status information and last date for assessment for superseded versions

Process	Version	Date	Last Date for Assessment
Registration	1	19 June 1995	31 December 2016
Revision	2	7 August 1997	31 December 2016
Revision	3	8 May 2001	31 December 2016
Review	4	20 June 2006	31 December 2016
Review	5	24 October 2014	31 December 2016
Revision	6	21 July 2016	31 December 2022
Review	7	23 July 2020	N/A
Rollover and Revision	8	26 April 2024	N/A

<b>Consent and Moderation Requirements (CMR) reference</b>	0028
--	------

This CMR can be accessed at <http://www.nzqa.govt.nz/framework/search/index.do>.

#### Comments on this unit standard

Please contact Ringa Hora Services Workforce Development Council [qualifications@ringahora.nz](mailto:qualifications@ringahora.nz) if you wish to suggest changes to the content of this unit standard.