

Identify levels of finish, calculate quantities and order stopping compounds for fibrous plaster work

Level 3

Credits 4

Purpose People credited with this unit standard are able to identify levels of finish for fibrous plaster walls and ceilings; and calculate the quantities of materials required and prepare an order.

Subfield Construction Trades

Domain Fibrous Plaster

Status Registered

Status date 25 January 2008

Date version published 25 January 2008

Planned review date 31 December 2011

Entry information Open.

Accreditation Evaluation of documentation and visit by NZQA and industry.

Standard setting body (SSB) Building and Construction Industry Training Organisation

Accreditation and Moderation Action Plan (AMAP) reference 0048

This AMAP can be accessed at <http://www.nzqa.govt.nz/framework/search/index.do>.

Special notes

- 1 Definition
Specifications refers to documented instructions (oral, written, graphic) and may include any of the following: manufacturer's specifications recommendations or technical data sheets; material specifications; specifications from a specialist source such as an architect, designer, engineer or a supervisor; site or work specific requirements.
- 2 Reference material AS/NZS 2589:2007 *Gypsum linings – Application and finishing*, available from Standards NZ (<http://www.standards.co.nz>).

- 3 Credit for this unit standard indicates compliance with industry practice. *Industry practice* refers to the ability to demonstrate knowledge and skills that reflect the productivity, uniformity, finish quality and material economies currently accepted within industry.

Elements and performance criteria

Element 1

Identify levels of finish for fibrous plaster walls and ceilings.

Performance criteria

- 1.1 Levels of finish for fibrous plaster work are described as specified by AS/NZS 2589:2007.
- 1.2 The description identifies stopping compounds required to achieve the specified levels of finish.

Element 2

Calculate the quantities of materials required and prepare an order.

Performance criteria

- 2.1 Area to be stopped is identified from working drawings or job specifications.
- 2.2 Quantities of materials are calculated, and an order is prepared to the nearest unit of supply.

Please note

Providers must be accredited by NZQA, or an inter-institutional body with delegated authority for quality assurance, before they can report credits from assessment against unit standards or deliver courses of study leading to that assessment.

Industry Training Organisations must be accredited by NZQA before they can register credits from assessment against unit standards.

Accredited providers and Industry Training Organisations assessing against unit standards must engage with the moderation system that applies to those standards.

Accreditation requirements and an outline of the moderation system that applies to this standard are outlined in the Accreditation and Moderation Action Plan (AMAP). The AMAP also includes useful information about special requirements for organisations wishing to develop education and training programmes, such as minimum qualifications for tutors and assessors, and special resource requirements.

Comments on this unit standard

Please contact the Building and Construction Industry Training Organisation national.office@bcito.org.nz if you wish to suggest changes to the content of this unit standard.